## TECHNICAL SHEET

## FINISHING AND GROOVING HAMMER Réf.: 0314350301

## **Caracteristics**

Curved failure. High carbon steel head C45E. Forged head, with induction heat treatment of working surfaces (54 HRC). Working parts and finely polished cheeks. Epoxy powder paint by electrostatic process, followed by baking. Red ring that signs the hammers Mob wooden handle. Deposited model. Hickory handle, from North America. Essence with recognized mechanical qualities and adapted to tool handles. Very high density. Superior mechanical resistance, especially to shocks. High flexibility, contributing notably to the whip and the absorption of vibrations. Pressed by a hydraulic machine, a force sensor measures on each product unitarily the power of fitting, then a pressure sensor controls the placement of the resin. Pullout performance is much higher than standard and is the hallmark of MOB tooling.



## **Product data**

B mm	C mm	C1 mm	A mm	L mm	✓ g	G	Artikelnr.	Repla- cement handle			EAN Code
43	8	20	160	280	350	G10	0314350301	6603	11	1	3303800314009



**NOVALIA SAS** 2 rue de Bergognon 42500 LE CHAMBON F. FRANCE - www.novalia.pro

PEDDINGHAUS Handwerkzeuge In der Graslake 35 58332 Schwelm DEUTSCHLAND - www.peddinghaus.de NOVALIA SA Str. Narciselor nr.50 500251 - Brașov ROMÂNIA

NOVALIA ESPAÑA Portuetxe 51, of.204 20018 San Sebastián