

CLICK TYPE PULLEY Réf.: 824260

Characteristics

Allows the lifting of all types of construction materials, scaffolding elements, etc. on the construction site

SAFETY ASSURED

- Self-locking system for improved safety
- Lifting notch by notch to protect the back
- Maintenance free
- Unadjustable (lock nuts)

TECHNICAL DATA

- Maximum working load (CMU): 100 kg
- Dimensions: L235 x H430 x E70 mm
- Anti-corrosion finish by electro-galvanizing
- Hanging point capacity: 100 kg
- Polyamide sheave Ø: 210 mm
- Used with ropes from Ø 20 to 26 mm (Ø 20/22 recommended)
- Weight: 3.4kg
- CE conformity

USE

Ratcheting system that allows you to recover while lifting the load. When you stop pulling on the rope, a pawl blocks the sheave and its trapezoidal groove slows down the sliding of the rope. Another pull unlocks the ratchet and you can continue to hoist or lower the load.



Product data



NOVALIA SAS 2 rue de Bergognon 42500 LE CHAMBON F.
FRANCE - www.novalia.pro

PEDDINGHAUS Handwerkzeuge In der Graslake 35
58332 Schwelm DEUTSCHLAND - www.peddinghaus.de

NOVALIA SA Str. Narciselor nr.50 500251 - Braşov ROMÂNIA
www.mob-ius.ro

NOVALIA ESPAÑA Portuete 51, of.204 20018 San Sebastián

CLICK TYPE PULLEY Réf.: 824260

Dim mm	sheave mm		 kg	G	Artikelnr.		EAN Code
235 x 430 x 70	210	100	3,4		824260	1	3479138242601



MONDELIN

NOVALIA SAS 2 rue de Bergognon 42500 LE CHAMBON F.
FRANCE - www.novalia.pro

PEDDINGHAUS Handwerkzeuge In der Graslake 35
58332 Schwelm DEUTSCHLAND - www.peddinghaus.de

NOVALIA SA Str. Narciselor nr.50 500251 - Braşov ROMÂNIA
www.mob-ius.ro

NOVALIA ESPAÑA Portuetxe 51, of.204 20018 San Sebastián