



DUPLI-BOLT CUTTER, ADJUSTABLE Réf.: 0518045001

Caracteristics

PERFORMANCE OF CUTTING: axial cutting. Cutting capacity up to 16 mm diameter. Long lasting forged blades. High resistance chrome-vanadium-molybdenum steel. Hardened and forged blades for a long lasting quality (cutting zone hardness: 56 to 60 HRC). Exclusive geometry (axis brought out of the center) for a bigger opening. Screwed heads for a higher compactness of bolts. Protection film against any untimely screw off. **QUALITY FINISH:** Epoxy paint boiled in furnace for an excellent resistance, 60µm thickness guaranteed. Sheathed elastomer handles for a good grip and a higher ergonomomy. Light tube arms. **SIMPLICITY OF USE:** adjusting of the blades distance using an eccentric screw. The change of blades is done by 2 screws.



Product data

| L mm | Thickness mm | Maximum of cutting capacity 80 daN/mm ² | Maximum of cutting capacity 140 daN/mm ² | Nr. |  g | G | Old Ref. Mondelin | ArtikeInr. |  | EAN Code | |
|------|--------------|--|---|------|---|------|-------------------|------------|---|----------|---------------|
| 450 | 130 | 35 | Ø 8 | Ø 6 | 0 | 1500 | G30 | 303470 | 0518045001 | 1 | 3303800004009 |
| 600 | 135 | 40 | Ø 10 | Ø 8 | 1 | 2570 | G30 | 303630 | 0518060001 | 1 | 3303800007659 |
| 750 | 135 | 43 | Ø 13 | Ø 9 | 2 | 4050 | G30 | 303780 | 0518075001 | 1 | 3303800007949 |
| 900 | 135 | 47 | Ø 14 | Ø 10 | 3 | 6235 | G30 | 303930 | 0518090001 | 1 | 3303800007956 |
| 1050 | 170 | 53 | Ø 16 | Ø 12 | 4 | 9025 | G30 | 303980 | 0518105001 | 1 | 3303800007963 |



NOVALIA SAS 2 rue de Bergognon 42500 LE CHAMBON F.
FRANCE - www.novalia.pro

PEDDINGHAUS Handwerkzeuge In der Graslake 35
58332 Schwelm DEUTSCHLAND - www.peddinghaus.de

NOVALIA SA Str. Narciselor nr.50 500251 - Braşov ROMÂNIA
www.mob-ius.ro

NOVALIA ESPAÑA Portuetxe 51, of.204 20018 San Sebastián